

Safety Data Sheet

Issue Date: 12-Sep-2017

Revision Date: 15-Sep-2017

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Stainless Steel Fiber

Other means of identification

SDS # INTRA-006

Product Code 316 stainless, 304, 310s, 347, Haynes 556, Hastelloy X, Hastelloy C22, FeCrAl

Recommended use of the chemical and restrictions on use

Recommended Use The manufacture of substances, composites, and nonwovens.

Details of the supplier of the safety data sheet

Supplier Address

IntraMicron, Inc.
368 Industry Dr.
Auburn, AL 36832

Emergency Telephone Number

Company Phone Number 334-502-2973
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Physical state Solid

Classification

Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

Signal Word

Danger

Hazard statements

May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Wear protective gloves/protective clothing/eye protection/face protection
 Contaminated work clothing must not be allowed out of the workplace
 Do not breathe dust/fume/gas/mist/vapors/spray
 Wash face, hands and any exposed skin thoroughly after handling
 Do not eat, drink or smoke when using this product

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF ON SKIN: Wash with plenty of water and soap
 Wash contaminated clothing before reuse
 If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Very toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%
Iron	7439-89-6	50-60
Nickel	7440-02-0	10-20
Chromium	7440-47-3	10-20
Molybdenum	7439-98-7	1-10
Manganese	7439-96-5	1-10
Silicon	7440-21-3	<5
Copper	7440-50-8	<5
Aluminum	7429-90-5	<5

**If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret. **

4. FIRST AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	Remove to fresh air.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects

Symptoms	May cause an allergic skin reaction. May cause cancer. Causes damage to organs through prolonged or repeated exposure.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental precautions

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing and eye/face protection. Contaminated work clothing must not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Nickel 7440-02-0	TWA: 1.5 mg/m ³ inhalable particulate matter	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 10 mg/m ³ IDLH: 10 mg/m ³ Ni TWA: 0.015 mg/m ³ TWA: 0.015 mg/m ³ except Nickel carbonyl Ni

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Chromium 7440-47-3	TWA: 0.5 mg/m ³	TWA: 1 mg/m ³ (vacated) TWA: 1 mg/m ³	IDLH: 250 mg/m ³ TWA: 0.5 mg/m ³
Manganese 7439-96-5	TWA: 0.02 mg/m ³ respirable particulate matter TWA: 0.1 mg/m ³ inhalable particulate matter TWA: 0.02 mg/m ³ Mn respirable particulate matter TWA: 0.1 mg/m ³ Mn inhalable particulate matter	(vacated) TWA: 1 mg/m ³ fume (vacated) STEL: 3 mg/m ³ fume (vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ fume Ceiling: 5 mg/m ³ Mn	IDLH: 500 mg/m ³ IDLH: 500 mg/m ³ Mn TWA: 1 mg/m ³ fume TWA: 1 mg/m ³ Mn STEL: 3 mg/m ³ STEL: 3 mg/m ³ Mn
Molybdenum 7439-98-7	TWA: 10 mg/m ³ inhalable particulate matter TWA: 3 mg/m ³ respirable particulate matter TWA: 10 mg/m ³ Mo inhalable particulate matter TWA: 3 mg/m ³ Mo respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ (vacated) TWA: 10 mg/m ³ Mo	IDLH: 5000 mg/m ³ IDLH: 5000 mg/m ³ Mo
Silicon 7440-21-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist IDLH: 100 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust TWA: 5 mg/m ³ Al
Tungsten 7440-33-7	TWA: 3 mg/m ³ respirable particulate matter TWA: 3 mg/m ³ W respirable particulate matter in the absence of cobalt	(vacated) TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³ W (vacated) STEL: 10 mg/m ³ (vacated) STEL: 10 mg/m ³ W	TWA: 5 mg/m ³ TWA: 5 mg/m ³ W STEL: 10 mg/m ³ STEL: 10 mg/m ³ W

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Solid	Odor	Not determined
Appearance	Not determined	Odor Threshold	Not determined
Color	Not determined		

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Iron 7439-89-6	= 30 g/kg (Rat)	-	-
Nickel 7440-02-0	> 9000 mg/kg (Rat)	-	-
Manganese 7439-96-5	= 9 g/kg (Rat)	-	-
Silicon 7440-21-3	= 3160 mg/kg (Rat)	-	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.

Carcinogenicity May cause cancer.

Chemical Name	ACGIH	IARC	NTP	OSHA
Nickel 7440-02-0		Group 2B	Known Reasonably Anticipated	X

Legend

- IARC (International Agency for Research on Cancer)*
- Group 2B - Possibly Carcinogenic to Humans*
- NTP (National Toxicology Program)*
- Known - Known Carcinogen*
- Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen*
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)*
- X - Present*

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral) 15,862.00 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Iron 7439-89-6		13.6: 96 h <i>Morone saxatilis</i> mg/L LC50 static	
Nickel 7440-02-0	0.174 - 0.311: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static 0.18: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50	1.3: 96 h <i>Cyprinus carpio</i> mg/L LC50 semi-static 10.4: 96 h <i>Cyprinus carpio</i> mg/L LC50 static 100: 96 h <i>Brachydanio rerio</i> mg/L LC50	100: 48 h <i>Daphnia magna</i> mg/L EC50 1: 48 h <i>Daphnia magna</i> mg/L EC50 Static

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Copper 7440-50-8	0.0426 - 0.0535: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 0.031 - 0.054: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	0.3: 96 h Cyprinus carpio mg/L LC50 semi-static 0.052: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.8: 96 h Cyprinus carpio mg/L LC50 static 0.3: 96 h Pimephales promelas mg/L LC50 static 1.25: 96 h Lepomis macrochirus mg/L LC50 static 0.112: 96 h Poecilia reticulata mg/L LC50 flow-through 0.0068 - 0.0156: 96 h Pimephales promelas mg/L LC50 0.2: 96 h Pimephales promelas mg/L LC50 flow-through	0.03: 48 h Daphnia magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Not determined

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Chromium 7440-47-3		Included in waste streams: F032, F034, F035, F037, F038, F039	5.0 mg/L regulatory level	
Nickel 7440-02-0		Included in waste streams: F006, F039		

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Chromium 7440-47-3	Toxic Corrosive Ignitable
Nickel 7440-02-0	Toxic powder Ignitable powder
Manganese 7439-96-5	Ignitable powder
Molybdenum 7439-98-7	Ignitable powder
Copper 7440-50-8	Toxic
Aluminum 7429-90-5	Ignitable powder
Titanium 7440-32-6	Ignitable powder

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT Not regulated

IATA Not regulated

IMDG
Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/E LINCS	ENCS	IECSC	KECL	PICCS	AICS
Iron	X	X	X		X	Present	X	X
Chromium	X	X	X		X	Present	X	X
Nickel	X	X	X		X	Present	X	X
Manganese	X	X	X		X	Present	X	X
Molybdenum	X	X	X		X	Present	X	X
Copper	X	X	X		X	Present	X	X
Silicon	X	X	X		X	Present	X	X
Aluminum	X	X	X		X	Present	X	X
Titanium	X	X	X		X	Present	X	X
Tungsten	X	X	X		X	Present	X	X

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*
- AICS - Australian Inventory of Chemical Substances*

US Federal Regulations

CERCLA

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Chromium 7440-47-3	5000 lb 10 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ RQ 10 lb final RQ RQ 4.54 kg final RQ
Nickel 7440-02-0	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Copper 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Nickel - 7440-02-0	7440-02-0	10-20	0.1
Chromium - 7440-47-3	7440-47-3	10-20	1.0
Manganese - 7439-96-5	7439-96-5	1-10	1.0

Chemical Name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Aluminum - 7429-90-5	7429-90-5	<5	1.0
Copper - 7440-50-8	7440-50-8	<5	1.0

CWA (Clean Water Act)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Chromium		X	X	
Nickel		X	X	
Copper		X	X	

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Nickel - 7440-02-0	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Nickel 7440-02-0	X	X	X
Chromium 7440-47-3	X	X	X
Manganese 7439-96-5	X	X	X
Molybdenum 7439-98-7	X	X	X
Copper 7440-50-8	X	X	X
Silicon 7440-21-3	X	X	X
Aluminum 7429-90-5	X	X	X
Titanium 7440-32-6	X		
Tungsten 7440-33-7	X	X	X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined
HMIS	Health Hazards	Flammability	Physical hazards	Personal Protection
	Not determined	Not determined	Not determined	Not determined

Issue Date: 12-Sep-2017
 Revision Date: 15-Sep-2017
 Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet